



*Ergo X-Treme™ is our safest and toughest ergonomic solution for harsh environments!*

- As a performance collection product, this mat offers maximum durability in wet or oily environments
- Modular tiles offer flexibility to reconfigure the mat to accommodate changing work environments
- Durable mat with an efficient drainage system for good adherence on oily surfaces

**ERGO X-TREME™ APPLICATIONS**

Provide a heavy-duty solution for oily areas e.g.: Factory, Machine shop, Auto manufacturer, Power transmission facility

**FEATURES**

- 100% oil and grease proof molded nitrile matting
- Aggressively patterned top surface ensures maximum foot traction in slippery environments
- Modular tiles can be assembled to fit any area

Compare [Ergo X-Treme™](#) to other Crown products:

 **ANTI-FATIGUE** **3/10**
 **DURABILITY** **10/10**
 **TRACTION** **10/10**



# 775 SOLID TOP



# 776 DRAIN OPENING




# 777 DRAIN OPENING WITH GRIT-SAFE™



# 779 BLACK WITH OPEN DRAIN WITH GRIT-SAFE™

INSTALLATION



**AVAILABILITY**

**TILES**

**18" X 18"**  
(8 tile case)

**PRE-CONSTRUCTED**

**3' X 4.5'**  
**3' X 6'**  
**3' X 9'**

(Includes 2 corners, 2 borders on the short side and 1 border on the length)

**CUSTOM CUTS**

**Unavailable**

**USE AND CARE**

**Damp mop and pressure hose**

**TECHNICAL DATA**

Description: 100% Nitrile rubber  
 Flammability: D.O.C.- F.F.-1-70 (Pill Test)  
 Electrical Properties: (10<sup>9</sup> ohms per sq.) ASTM D-257  
 Coefficient of friction: # 775 -Solid Top - .965 per ASTM D1677  
 # 776 -Drainage Top - .965 per ASTM D1677  
 # 777 -Drainage Top with Grit-Safe 1.08 per ASTM D1677

**PROFILE**



**Thickness: 3/4"**

**WARRANTY**



**TOTAL CONFIDENCE WARRANTY**

Click or scan code for short video



AUTHORIZED DISTRIBUTOR